


SPECIFICATION CONTROL DRAWING



NOTES

1) D6021-XXX CROSSTUBE
LENGTH

WHERE XXX IS LENGTH IN INCHES
EG. 125" LONG TUBE: D6021-125

2) MATERIAL: 17-4PH SEAMLESS STEEL TUBE PER ASTM A564
 $\text{Ø}2.378$ O.D. x $\text{Ø}1.980$ I.D.

HEAT TREAT TO:
MIN. ULTIMATE TENSILE STRENGTH = 150 ksi
MIN. YIELD TENSILE STRENGTH = 140 ksi
MAX. YIELD TENSILE STRENGTH = 160 ksi

3) TOLERANCES ARE AS FOLLOWS:
ECCENTRICITY: 15% (+/-0.030" WALL)
LENGTH: XXX +0.188"/-0.000"
STRAIGHTNESS: 0.012" DEVIATION / 12" LENGTH

4) ALL DIMENSIONS ARE IN INCHES
5) TUBE MUST BE PICKLED OR ELECTROPOLISHED TO BE SMOOTH AND FREE FROM SCALE.
6) EXTREME CARE MUST BE TAKEN TO PROTECT THE OUTSIDE SURFACE OF THE TUBE. THE OUTSIDE SURFACE MUST BE SMOOTH AND FREE FROM SURFACE DEFECTS SUCH AS SCRATCHES, NICKS, OR DENTS. DEFECTS UP TO 0.005" MAY BE BLENDED OUT LONGITUDINALLY. CIRCUMFERENTIAL GRIND MARKS ARE UNACCEPTABLE.

PRELIMINARY ISSUE

CP 12/9/12

PA4	NEW ISSUE	CP	12.09.12
REV.	DESCRIPTION	BY	DATE
DESIGN	CP	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	CP		
CHECKED		DRAWING NO.	REV. PA4
MFG. APPR.		D6021	SHEET 1 OF 1
APPROVED		TITLE	SCALE
DE APPR.		CROSSTUBE MATERIAL	NTS
DATE	12.09.12	COPYRIGHT © 2012 BY DART AEROSPACE LTD <small>THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</small>	